

64a 705



(11)

PATENT SPECIFICATION ⁽²¹⁾ 38,214/68

Class ⁽⁵²⁾ 57.5.

Int. Cl. ⁽⁵¹⁾ B65d.

Application Number ⁽²¹⁾ 38214/68.

Lodged ⁽²²⁾ 23rd May, 1968.

Complete Specification
entitled ⁽⁵⁴⁾ SCREW CAP WITH LOCKING MEANS.

Lodged ⁽²³⁾ 23rd May, 1968.

Accepted ⁽⁴⁴⁾ Lapsed under Section 47c(b).

Published ⁽⁴¹⁾ 27th November, 1969.

Convention Priority ⁽³⁰⁾

Applicant ⁽⁷¹⁾ ALRIK LIVER LINDSTROM.

Actual Inventor ⁽⁷²⁾ ALRIK LIVER LINDSTROM.

Related Art ⁽⁵⁶⁾

The following statement is a full description of this invention, including the best method of performing it known
to us

14888/72-4

L88-69-1D-8P.C.

F. D. Atkinson, Government Printer, Canberra

38,214 /68

This invention relates to a screw cap of the type comprising one or more sealing flanges projecting from the top of the cap for cooperation with the end of the mouth wall of a bottle or the like.

Screw caps of this type have an effective sealing capability after they have been screwed onto a bottle and also during some time afterwards. However, after bottles provided with screw caps have been stored for some time the cap has a tendency to become less tight, probably because of cold flow of the material of the cap which usually consists of a thermoplastic material, resulting in that the bottle will not be tightly closed.

It has been found that the cap can be considerably better secured to the bottle if in accordance with this invention a sealing flange or an additional flange extends in close proximity to the wall of the cap, whereby to effect an elastic attachment of the screwed cap due to engagement of the flange with the outside of the mouth wall of the bottle or the like and with the wall of the cap. Tests have proved that in case of equal tightening moments the moment required for unscrewing a screw cap according to the invention from a bottle is about 75 % greater than the corresponding moment required for unfastening a conventional screw cap having sealing flanges only.

The invention is now described more closely with reference to the annexed drawing in which

Fig. 1 is a sectional view of a screw cap provided with a lock flange and

Figs. 2a and 2b are sectional views of screw caps according to the invention having different conceivable configurations of sealing flanges.

38,214/68

By way of example, the screw cap illustrated in Fig. 1 is made by injection moulding a thermoplastic material. The top of the cap is formed with a thin sealing flange 2 which is concentric with the cap. The purpose of this sealing flange is to effect a tight closure of a bottle or the like, not shown, by engaging the inner edge of the mouth wall of the bottle. As mentioned above, the sealing effect is satisfactory as long as the screw cap remains reliably screwed onto the bottle. However, if the screw cap becomes less tight after the bottle has been stored for some time the sealing will no longer be effective. In order to prevent the screw cap from getting loose, there is provided a lock flange 4 in close proximity to the wall of the cap as shown in Fig. 1. The lock flange need not necessarily serve as a sealing member. When the cap is being screwed onto the bottle, not shown, the outside of the mouth wall of the bottle will elastically force the flange 4 toward the wall of the cap and slightly upwardly, with the result that after the cap has been completely screwed onto the bottle an elastic locking action will be obtained between the cap and the bottle.

Figs. 2a and 2b illustrate examples of an additional sealing flange 6 and 8, respectively, which may be provided in a screw cap according to the invention for obtaining a larger sealing area in a manner known per se.

Many different embodiments of the screw cap according to the invention are conceivable to meet various requirements such as to the selection of the material of the screw cap. The lock flange need not necessarily extend along a closed line. It may be replaced by a plurality of shorter flanges located on a common circular line close to the inner wall of the cap.

38,214 /68

These shorter flanges need not necessarily have the same radius of curvature as said circular line.

In the production of bottles which are to be provided with a lock flange according to the invention the moulds used therefore can in a suitable way be so worked that the almost inevitably unsymmetrical and uneven shape of the outside of the mouth wall is further emphasized, by means of which the effect of the lock flange is further supported.

THE CLAIMS DEFINING THE INVENTION ARE AS FOLLOWS:

38.214 /68

1. A screw cap comprising one or more sealing flanges projecting from the top of the cap for cooperation with the end of the mouth wall of a bottle or the like, characterized in that, a sealing flange or an additional flange extends in close proximity to the wall of the cap, whereby to effect an elastic attachment of the screwed cap due to engagement of the flange with the outside of the mouth wall of the bottle or the like and with the wall of the cap.

23 MAY 1968

2. A screw cap as claimed in claim 1, characterized in that, said additional flange is a lock flange which extends substantially circularly through an angle of at least 180° along the wall of the cap.

23 MAY 1968

3. A screw cap as claimed in claim 2, characterized in that the lock flange extends along a closed circle.

23 MAY 1968

4. A screw cap as claimed in claim 1, characterized in that, said additional flange consists of a plurality of lock flanges extending along a common curved line.

23 MAY 1968

5. A screw cap as claimed in claim 4, characterized in that the lengths of the radii of curvature of the lock flanges are different from the distances between the flanges and the centre of the cap.

38,214 /68

6. A screw cap substantially as described with reference to Fig. 1, Fig. 2a or Fig. 2b of the accompanying drawing.

23 MAY 1968

DATED this 21st Day of May, 1968

ALRIK CIVER LINDSTROM

By his Patent Attorneys,
CLEMENT HACK & CO.

Fellows Institute of Patent
Attorneys of Australia.

26

38,214/68

FIG.1





FIG.2a



FIG.2b



38,214 /68

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☒ FADED TEXT OR DRAWING
- ☒ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☒ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.